



Dati tecnici Technical data Datos técnicos Données techniques Technische Daten	Tensione di alimentazione: <i>Supply voltage:</i>	12 Vdc	Temperatura di esercizio: <i>Working temperature:</i>	-20°C ~ +50°C
	Omologazione: <i>Homologation:</i>	ECE E3 2381 E3 148R00 21292	Tecnologia: <i>Light technology</i>	LAMPADINA BULB
	Connessioni elettriche: <i>Electrical wirings:</i>	Connettore 5 vie 5-ways connector + 4wys aux	IP rating:	n.d.
	Materiali: <i>Material</i>	Foro passacavo with cable grommet PP20T – PMMA - PC	Dimensioni: <i>Dimensions</i>	Interasse di fissaggio: <i>Fixing distance</i>

		Sinistro <i>Left</i>	Destro <i>Right</i>	Posizione <i>Tail</i>	Stop	Direzione <i>Direction</i>	Luce targa <i>Nr Plate light</i>	Retronebbia <i>Fog light</i>	Retromarcia <i>Reverse light</i>	Laterale <i>Side marker</i>	Catadiottro <i>Reflector</i>
	5 ways conn + 4ways aux	2800/2	✓	✓	✓	✓		✓			✓
		2800/2DK	✓		✓	✓					✓
		2800/2L	✓		✓	✓		✓			✓
		2800/10	✓		✓	✓	✓	✓			✓
		2800/12	✓		✓	✓	✓		✓		✓
	5 ways connector + 4ways aux	2800/3		✓	✓	✓		✓			✓
		2800/5		✓	✓	✓			✓		✓
		2800/5L		✓	✓	✓			✓		✓
		2800/11		✓	✓	✓	✓				✓
		2800/11UK		✓	✓	✓	✓	✓			✓
		2800/13		✓	✓	✓	✓		✓		✓
	With cable grommet	2800/2F	✓		✓	✓		✓			✓
		2800/12F	✓		✓	✓	✓		✓		✓
		2800/10F	✓		✓	✓	✓	✓			✓
		2800/3F		✓	✓	✓	✓	✓			✓
		2800/5F		✓	✓	✓	✓		✓		✓
		2800/11F		✓	✓	✓	✓	✓			✓
		2800/13F		✓	✓	✓	✓		✓		✓