



Dati tecnici Technical data Datos técnicos Données techniques Technische Daten	Tensione di alimentazione: <i>Supply voltage:</i>		12 Vdc		Temperatura di esercizio: <i>Working temperature:</i>		-20°C ~ +50°C	
	Omologazione: <i>Homologation:</i>		ECE E3 2732		Tecnologia: <i>Light technology</i>		LAMPADINA <i>BULB</i>	
	Connessioni elettriche: <i>Electrical wirings:</i>		2 ways connector		IP rating:		n.d.	
	Materiali: <i>Material</i>		PA66 – PMMA – PC		Dimensioni: <i>Dimensions</i>		Approx. 231 x 100 x 40 mm	
	Led	Lampadina <i>Bulb</i>	Cavo (mm) <i>Cable (mm)</i>	Connessione <i>connector</i>	Rubacorrente <i>Fast clip</i>	Sinistr <i>Left</i>	Destro <i>Right</i>	Vetrino nero <i>Black lens</i>
940/DX		✓		RD 2 way	✓		✓	
940/DX L.1500		✓	1500	RD 2 way			✓	
940/DX L.600		✓	600	RD 2 way			✓	
940/DX L.730		✓	730	RD 2 way			✓	
940/DX-2N		✓		RD 2 way	✓		✓	✓
940/DX-N		✓		RD 2 way	✓		✓	✓
940/DX-NL		✓					✓	✓
940/IMB-800DX		✓	800		✓		✓	
940/IMB-800SX		✓	800		✓	✓		
940/S		✓						
940/SX		✓				✓		
940/SX L.1500		✓	1500			✓		
940/SX L.600		✓	600			✓		
940/SX L.730		✓	730			✓		
940/SX-2N		✓				✓		✓
940/SX-N		✓				✓		✓
940/SX-NL		✓				✓		✓
940-2N-IT		✓						✓
940-L150DX		✓	150				✓	
940L-150DX		✓	150				✓	
940-L150SX		✓	150			✓		
940L-150SX		✓	150			✓		

Combinazioni di lunghezza cavo e/o connettori diversi disponibili su richiesta
 Different cable length and/or connector available on request